RØDECASTERDUO INTEGRATED AUDIO PRODUCTION STUDIO

The RØDECaster Duo is a compact and incredibly powerful all-in-one audio production solution for podcasters and content creators. It features two combo inputs with ultra-low-noise, high-gain Revolution Preamps™ for connecting both microphones and instruments, plus an integrated Series IV 2.4GHz wireless receiver for connecting RØDE wireless microphones, and a 3.5mm TRRS input for connecting a headset. Studio-grade APHEX® processing delivers superior audio quality, with perfectly tailored presets and flexible on-board editing making it easy to capture professional sounding recordings. Advanced Bluetooth® connectivity, dual USB-C interfaces, and Wi-Fi and Ethernet connections offer unrivalled integration with computers, smartphones, and other devices, and the fully customisable mixer allows the RØDECaster Duo to be configured to suit any application or setup. Six programmable SMART pads can be used to trigger everything from sounds and voice effects to mixer actions and MIDI for unmatched creative flexibility and control. The RØDECaster Duo is also incredibly simple to use, with a large high-resolution touchscreen and rotary encoder for easy navigation, intuitive controls, and professionally tailored presets.

- Fully integrated audio production studio for podcasters and content creators
- Ultra-low-noise, high-gain Revolution Preamps™ (-131.5dBV EIN, 76dB gain)
- Two high-quality Neutrik[®] combo inputs for connecting microphones, instruments and line-level devices
- Seven individually assignable channels with four broadcastquality physical faders and three virtual faders
- High-performance quad-core audio engine
- Studio-grade APHEX[®] audio processing and on-board effects
- Six fully programmable SMART pads with bank switching

- Dual USB-C interfaces for connecting two computers or mobile devices
- Advanced Bluetooth® connectivity for high-quality phone call integration
- Multitrack or stereo recording to a microSD[™] card, USB storage device or computer
- Two high-power headphone outputs, one TRRS headset output and two balanced ¼-inch line outputs
- 5.5-inch high-definition touchscreen with haptic feedback and rotary encoder for easy navigation and control
- Designed and made in RØDE's precision facilities in Sydney, Australia















White

ACOUSTIC, VIDEO & ELECTRICAL SPECIFICATIONS

| Frequency Range: | Mic Inputs: 20Hz - 20kHz Monitor Outputs: 20Hz - 20kHz |
|---------------------------------------|---|
| Microphone Input Impedance: | 4ΚΩ |
| Instrument Input Impedance: | 1ΜΩ |
| Preamplifier Gain Range: | 0 - 76dB |
| Equivalent Noise: | -131.5dBV (A-weighted) |
| Line Output Maximum Level: | 4dBu |
| Headphone Output Power: | 250mW |
| Power Requirements: | USB-C PD (9V, 3A) |
| Analogue Audio Input Connectivity: | 2 x combo jack (mic, instrument, line) 1 x 3.5 TRRS headset jack (I/O) |
| USB Interface 1: | 1 x 2-in/14-out multichannel device, 1 x 2-in/2-out with mix-minus |
| USB Interface 2: | 1 x 2-in/2-out with mix-minus |
| Bit Depth: | 24-bit |
| Sample Rate: | 48kHz |
| Recording Storage: | microSDHC, microSDXC, USB-C removable drive (exFAT – minimum 100MB/s) |



ACOUSTIC, VIDEO & ELECTRICAL SPECIFICATIONS

WHATS IN THE BOX

| Data Transfer: | USB 3.0 SD card reader 130MB/s |
|------------------------|---|
| Network Connectivity: | WiFi 802.11g/n/ac 2.4GHz and 5GHz, Ethernet 100/100 |
| Internal Storage (GB): | 4GB (SMART pads) |
| OS Requirements: | macOS 10.15 or later, Windows 10 Version 1803 or later, Windows 11 |
| | |





MECHANICAL SPECIFICATIONS

| Weight (grams): | 1131g |
|------------------------------|--|
| Dimensions (millimetres): | Length: 235mm Width: 225mm Height: 76 mm |
| Compatible RØDE Accessories: | RØDECaster DUO Power Adapter SC27 USB-C to USB-C Cable |
| Included Software: | RØDE Central |
| | |

RØDECaster DUO

Power adaptor



SC27 USB-C cable

DIMENSIONS



