RØDELink PERFORMER KIT

- $\bullet \;\;$ Includes TX-M2 microphone, RX-DESK receiver, RØDE LB-1 lithium-ion rechargeable battery
- Series II 2.4GHz digital transmission
- 128-Bit encrypted signal
- High-quality condenser microphone
- Up to 100m range*
- Power via LB-1 rechargeable battery (included)/AA battery
- Low handling noise
- Mute switch
- Designed and made in Australia



SERIES II 2.4GHZ DIGITAL TRANSMISSION





HIGH-QUALITY LB-1 LITHIUM-ION UP TO CONDENSER BATTERY (INCLUDED) 100M RANGE MICROPHONE OR AA BATTERY





ACOUSTIC & ELECTRICAL SPECIFICATIONS

Transmission type:	2.4GHz fixed frequency agile system
Dynamic range:	118dB
Range (distance):	Up to 100m*
Frequency range:	35Hz – 20kHz
Max output:	+18dBu level
Max input signal level:	140dB SPL
Max latency:	4ms

RECEIVER (RX-DESK)

Power source:	15v 1A DC Power Pack
Antenna:	External diversity antenna
Output Connection:	Balanced XLR/Unbalanced ¼" jack
Dimensions:	208mmW x 37mmH x 166mmD
Weight:	702gm





TRANSMITTER (TX-M2)

Power source:	2 x AA 1.5v Batteries or RØDE LB-1 4.2v Lithium-Ion Rechargeable Battery or 5v USB
Antenna:	Diversity antenna located at the bottom of TX-M2
Dimensions:	40mmW x 256mmH x 40mmD
Weight:	222gm
Weight:	702gm

WHAT'S IN THE BOX





RX-DESK Receiver

TX-M2 Wireless Microphone



Micro-USB Cable



DC Power Pack



Mic Clip




LB-1 lithium ion battery



ZP2

POLAR PATTERN



FREQUENCY RESPONSE

