

RØDELink Filmmaker Kit

AUSTRALIA
107 Carnarvon st, Silverwater NSW 2128 Australia
Ph: +61 2 9648 5855 Fx: +61 2 9648 2455

USA
PO Box 91028, Long Beach CA 90809-1028
Ph: +1 562 364 7400 Fax: +1 888 412 4664



Features

- Includes Transmitter (belt-pack mount), Receiver (camera or belt-pack mount) and Lavalier microphone (and translations smaller)
- Series II 2.4GHz digital transmission
- 128-bit encrypted signal
- Up to 100m range
- One touch pairing
- OLED digital display
- 3 level gain control
- Omnidirectional lavalier microphone
- AA Battery or USB Power
- Designed and made in Australia

General System Specs

Transmission type	2.4GHz fixed frequency agile system
System dynamic range	112dB
Range (distance)	100m
Frequency range	35Hz - 22kHz
Maximum output level	1v rms (2.8v p-p)
Max input signal level	1v rms (2.8v p-p)
Max latency	4ms

Receiver (RX-CAM)

Power source	2 x AA battery and micro USB
Antenna	Internal
Output connection	3.5mm TRS jack socket – dual mono with thread lock
Output impedance	300Ω
Dimensions	111mm H x 65mm W x 52mm D

Transmitter (TX-BELT)

Power source	2 x AA battery and micro USB
Antenna	Internal
Input connection	3.5mm TRS jack socket with thread lock
Input impedance	10kΩ
Dimensions	111mm H x 65mm W x 40mm D

Lavalier

Acoustic Principle	Pressure Gradient
Frequency Response	60Hz – 18kHz
Polar Pattern	Omni-directional
Maximum SPL	110 dB SPL (@ 1kHz, 1% THD into 1Ω load)
Sensitivity	-33.5db re 1 Volt/Pascal (21.00mV @ 94 dB SPL) +/- 2dB @ 1kHz
Dimensions	1200.00mmH x 4.50mmW x 4.50mmD

RØDE
MICROPHONES