

The Al-1 is a studio-grade audio interface suitable for connecting both microphones and musical instruments to a computer or tablet. It features an ultra-low-noise preamp, a high-power headphone amplifier, and balanced line outputs. Switchable 48V phantom power facilitates the connection of condenser microphones, and zero-latency monitoring mode allows for seamless recording.

- Single channel audio interface
- 2 x ¼" balanced line outputs
- $\bullet \quad \mathsf{Neutrik^{TM}} \ \mathsf{combo} \ \mathsf{jack} \ \mathsf{input}$
- 48V phantom power







1/4" BALANCED LINE OUTPUTS



NEUTRIK™ COMBO JACK INPUT





## ACOUSTIC & ELECTRICAL SPECIFICATIONS

Computer Connectivity:	USB
Form Factor:	Desktop
Simultaneous I/O:	1 x 2
Number of Preamps:	1
Phantom Power:	Yes
Bit Depth:	24-bit
Sample Rates:	44.1 kHz 48 kHz 88.2 kHz 96kHz
Analog Inputs:	1 x Neutrik XLR-1/4" combo
Analog Outputs:	$2 \times 1/4$ " (impedance balanced) $1 \times 1/4$ " (headphones)
Direct Monitor:	Yes
USB:	1 x USB Type C
Bus Powered:	Yes
OS Requirements:	Mac OS 10.10 or later Windows 7 or later
Power:	USB bus-powered





## MECHANICAL SPECIFICATIONS

## WHATS IN THE BOX

Weight (grams):	560
Dimensions	Depth: 100 Width: 124
(millimetres):	Height: 38 (with knobs, 88 without knobs)



Al1 Single Channel Audio Interface



USB-C to USB-A Cable

## DIMENSIONS



