VideoMic[™] NTG


ON-CAMERA SHOTGUN MICROPHONE

The VideoMic NTG is a feature-packed, broadcast-grade shotgun microphone optimised for on-camera use. Flat frequency response, tight polar pattern, and precision gain control ensure superior audio in any recording. An auto-sensing 3.5mm output interacts seamlessly with both cameras and mobile devices, and a USB output offers direct connectivity with a computer, tablet or phone for ultimate versatility.

- Highly directional shotgun microphone
- In-built rechargeable lithium-ion battery (30+ hours use)
- 3.5mm TRS / TRRS auto-sensing output for connection to cameras or mobile devices
- USB-C digital audio output compatible with computers, tablets and phones (SC-15 Lightning Accessory Cable required for connection to iOS devices)
- Pad, safety channel, HF boost, two stage high-pass filter











3.5mm TRS



ACOUSTIC & ELECTRICAL SPECIFICATIONS

Pressure gradient electret condenser
Supercardioid
20Hz – 20kHz
35Hz – 18kHz ±3 dB
10Ω
79 dBA
15dB SPL (A-weighted, as per IEC651)
105dB SPL (A-weighted, as per IEC651)
-31dBV(28.78mV @ 94dB SPL) ± 1dB @ 1kHz
120dB SPL
75Hz, 150Hz
30+ hours
350mAh
3.5mm auto-sensing USB-C
24-bit
48 kHz
macOS 10.15 Windows 10 (20H2) iOS 14 Android 9.0





MECHANICAL SPECIFICATIONS

WHATS IN THE BOX


Weight (grams):	94
Dimensions (millimetres):	Diameter: 21.6 Length: 171
Compatible RØDE Accessories:	SC19, SC18,SC16, SC15, SC11, VXLR Pro, WS11, Boompole
Compatible RØDE Software:	RØDE Central
Included Accessories:	1 x VideoMic NTG 1 x SM7-R 1 x SC10 1 x SC15 1 x SC16 1 x WSVM



DIMENSIONS



POLAR PATTERN



FREQUENCY RESPONSE

